

## STANDARD INFORMATION

**If the project requires any changes to the Certification Data Report outside of Section 1, then this SUN applies.**

**Standard:** UL 73

**Standard ID:** Motor-Operated Appliances [UL 73:2011 Ed.10+R:24Apr2024]

**Previous Standard ID:** Motor-Operated Appliances [UL 73:2011 Ed.10+R:06Oct2023]

## EFFECTIVE DATE OF NEW/REVISED REQUIREMENTS

**Effective Date:** **January 5, 2026**

## IMPACT, OVERVIEW, AND ACTION REQUIRED

**Impact Statement:** No action is required for currently certified products. If modifications to the product after the effective date require an evaluation and/or testing, then the product must undergo re-evaluation to the new requirements.

**Overview of Changes:** Addition of interlock requirements for commercial trash compactors and bailers. Specific details of new/revise requirements are found in table below.

***Current Listings Not Active? – Please immediately identify any current Listing Reports or products that are no longer active and should be removed from our records. We will do this at no charge as long as Intertek is notified in writing prior to the review of your reports.***



## STANDARD INFORMATION

| CLAUSE | VERDICT | COMMENT   |
|--------|---------|---|
|        |         | <i>Additions to existing requirements are <u>underlined</u> and deletions are shown <del>lined out</del> below.</i>   |
| 40     | Info    | <b>Specific Appliances</b>  |
|        |         | <b><i>New section added;</i></b>  |
| 40.3   |         | <b>Commercial trash compactors and bailers</b>  |
| 40.3.1 |         | Commercial trash compactors or bailers with a safety door or guard, which if opened may expose the user to any part capable of causing injury to persons, shall be interlocked as part of an interlock system.  |
|        |         | The interlock system shall:   |
| 40.3.2 |         | a) Disconnect power to the hazardous part immediately after the door, gate, or guard is opened;<br>b) Comply with the interlock switch requirements in Section 39;<br>c) Withstand 100,000 cycles of operation controlling a load not less than that controlled in the product and shall function normally upon completion of the test; and<br>d) Comply with the test specified in Section 65, Interlock System Endurance Test – Recessed Ultrasonic Cleaners and Commercial Trash Compactors and Bailers. |
| 65     | info    | <b>Interlock System Endurance Test – Recessed Ultrasonic Cleaners and Commercial Trash Compactors and Bailers</b>   |
|        |         | The interlock system of a recessed ultrasonic cleaner <u>and commercial trash compactors or bailers</u> shall be subjected to the endurance test described in 65.2 and 65.3. As a result of the test:   |
| 65.1   |         | a) There shall not be any electrical or mechanical malfunction of the interlock system, or undue pitting or burning of the switch contacts; and<br>b) The fuse in the grounding connection shall not open.  |